MODEL EL-1-FL

APPLICATION AND DESIGN:

The EL-1-FL is generally used as a decorative louver that is installed in PTAC applications. It consist of a Flanged Frame that can assist in installations or assist in the aesthetics of the Design. The free area is approximately 65% which provides minimal resistance to airflow. This grille is available with an optional split airflow design which allows discharge and return air to flow through the same grille simultaneously.

STANDARD CONSTRUCTION:

Frame: 0.063" [1.6mm], Flanged Frames #1 or #2, 6063-T5 Extruded Aluminum

Blade: 0.070" [1.78mm], 6063-T5 Extruded Aluminum placed centers on 0.75" [19.05mm] (available in 30° or 42°)

Blade Brace: 0.070" [1.78mm], 6063-T5 Extruded Aluminum, 16" [406mm] max o.c.

Finish: Mill Aluminum

Max Single Section: 120"w x 84"h [3048mm x 2134mm] _{0.425"}

(Multi-section Units Available)


OPTIONS:

- ☐ Flange Frame Design: ☐ #1, ☐ #2
- ☐ Blade Degree: ☐ 30°, ☐ 42°
- ☐ Insect Screen (Other Screens Available, See Screen Page)
- $\hfill \square$ Blade Direction: $\hfill \square$ Facing Up, $\hfill \square$ Facing Down
- ☐ Split Airflow Design: ☐ Design #1, ☐ Design #2
 - ☐ Return Height: _____"
- ☐ Stud/Bolt in Perimeter for Mounting
- ☐ Mounting Holes

AVAILABLE FINISHES:

- ☐ Durable Polyester (AAMA 2604)
- 70% PVDF Fluoropolymer (AAMA 2605)
- ☐ Yellow Primer
- ☐ Clear Anodize
- ☐ Dark Bronze Anodize

PTAC GRILLE WITH FLANGE FRAME



Note: Specify Blade Direction (Airflow), Cores can be

1.488"


[37mm]

Optional Stud/Bolt Mounting

[10.8mm]

Reversed.

Split Airflow Options



Qty.	"A" (width)	"B" (height)	"C ^a " (specify)	"D" (specify)	Tag

a "E" Not to Exceed 16" [406mm]

*Width and Height dimensions are approximately 1/4" [6.35mm] under listed size.

Due to continuing research, United Enertech reserves the right to change specifications without notice.



3005 South Hickory Street Chattanooga, Tennessee 37407 Tel: (423) 698-7715 Fax: (423) 698-6629 www.unitedenertech.com

MODEL EL-1-FL (PTAC Grille With Flange Frame)

	*		•	,
DRAWN BY:	DATE:	REV. DATE:	REV. NO.	DWG. NO.:
CLJ	5-24-10	4-6-20	2	A-43